MS4000 MINI-SIREN



The Federal Signal MS4000 series mini-siren is advanced, efficient, and economical. It offers value-packed, reliable performance with effective traffic clearing capability.

Years of design and manufacturing experience have made Federal Signal the leader in the electronic siren marketplace. Reliability is increased and operating temperature is decreased with the use of advanced rail circuitry and low-loss FET design arrangement. Efficiency and versatility are built-in features of the MS4000. This mini-siren comes with its own bracket and can be mounted virtually anywhere because of its compact size and lightweight construction.

MS4000 mini-sirens provide 100-watt output and meet Class A requirements when paired with any Federal Signal speaker. This minisiren can operate from any 12-volt negative ground vehicle electrical system. It is protected against failure modes, including reversed polarity, by a fuse that can be replaced without tools. The MS4000 can be powered via the vehicle's power distribution center or directly from the vehicle's battery.

Wail, Yelp, Priority, Manual, and Air Horn are all standard on the MS4000. Two rocker switches control all the siren functions. One switch controls AIR HORN/MANUAL, and the other controls WAIL/YELP. The AIR HORN/MANUAL switch rests in the neutral (center) position and activates a function when momentarily placed into the up or down position. The WAIL/YELP switch is a three-position switch with the center position being neutral.

A new, built-in *intersection clearing feature* adds effective traffic management capability at potentially hazardous crossings. When the MS4000 is activated and in the WAIL position, depressing the momentary switch to the MANUAL position produces an eight-second Yelp tone. When the MS4000 is activated and in the YELP position, depressing the momentary switch to the MANUAL position produces an eight-second Priority tone.

The MS4000U is designed especially for the undercover officer and volunteer firefighters. Siren functions are activated in the same manner as the standard MS4000, but from switches mounted onto a small, remote switch panel.

Intersection Clearing Feature

Depressing the momentary MANUAL switch activates additional alternate sounds.

Depressing MANUAL Produces

1. Switch set to WAIL

8-second Yelp tone

2. Switch set to YELP

8-second Priority tone

QUICK REFERENCE

FEATURES

- Economical.
- Small and compact mounts virtually anywhere.
- Easy to operate new, builtin intersection clearing feature.
- High reliability advanced circuitry and FET design.
- 100-watt output meets Class A with just one Federal Signal speaker.
- Output short circuit protected – replaceable fuse protection.
- Tones included Wail, Yelp, Priority, Manual (peak and hold), and Air Horn.

APPLICATIONS

- Police vehicles
- Fire chiefs
- Volunteer vehicles

APPROVAL

 Meets Class A requirements for sound output when paired with one Federal Signal 100-watt speaker

RELATED PRODUCTS

Flashers

Bulletin #3301

Grille Lights

Bulletin #4110

Speakers

Bulletin #6100

DynaMax[™] Speaker Bulletin #6102

How To Order

1. Specify model.

MS4000 100-watt electronic mini-siren with OR intersection clearing feature

MS4000U 100-watt electronic undercover

mini-siren with remote switches and

intersection clearing feature

2. Order optional equipment (if necessary).

MS100-01 100-watt DynaMax[™] speaker with standard bail bracket mount kit

MS100-02 100-watt DynaMax[™] speaker with

'95–'97 Ford Crown Victoria mount

kit

MS100-03 100-watt Dyna Max^{TM} speaker with

'95–'97 Chevy Lumina mount kit

MS100-04 100-watt DynaMax[™] speaker with '98 Ford Crown Victoria mount kit

MS100-05 100-watt DynaMax[™] speaker with

'98 Ford Explorer and Expedition

mount kit

MS100-06 100-watt DynaMax[™] speaker with

'96-'00 Chevy Tahoe mount kit

MS100-07 100-watt DynaMax[™] speaker with

'00 Chevy Impala mount kit

FA6 Solid-state brake/turn/tail/rear deck

flasher (2.4 flashes per second)

GS1 Compact strobe grille light,

adjustable 170° vertically and

360° horizontally

GH1 Compact halogen grille light, 25-watt

bulb draws just 2 amps when lit

SPECIFICATIONS
Power (watts)100
Input Voltage11-16 VDC
Standby Current<25 mA
Operating Current10 amperes maximum
Operating Temperature–30° C to 65° C
Dimensions
Height1.5 in. (3.8 cm)
Length 5.5 in. (14.0 cm)
Width6.5 in. (16.5 cm)
Shipping Weight2.5 lbs. (1.1 kg)